THIRD-ORDER LEVELING SEA LEVEL DATUM OF 1929 38-085-21
TAYLORSVILLE QUADRANGLE
171 KENTUCKY
N3800-W8515/15
DIAGRAM NJ 16-6
DR LOUISVILLE

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Bullitt, Jefferson, Shelby, and Spencer Counties

Final adjustment of 1973

Edition of 4/13/73


PR: DSW/dt

LOUISVILLE

(172)

Only the permanent marks are listed for lines run more than 25 years before edition date

LA GRANGE (188)



# NGS VERTICAL CONTROL DATA

- A. Quadrangle 380852
- \* Isolated bench mark

# INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (USGS)	PAGE NO.
455 468 513 522 KY 591 595 600 629 642 KY 685 KY 701 725 750 PTS NO 1 1905 825 PTS NO 4 1905 489 1 D 1923 KY 490 2 D 1923 KY 3 D 1923 KY 4 D 1923 KY 5 D 1923 KY 10 D 1923 KY 10 D 1923 KY 11 D 1923 KY 11 D 1923 KY	433933331233335454844445 7, 5,14844445	TT 58 DWP 1948 619 54 EOM 1949 612 55 EOM 1949 574 56 EOM 1949 756 58 EOM 1949 756 58 EOM 1949 564 60 EOM 1949 546 72 EOM 1949 683 TT 36 AS 1950 728 46 RHP 1952 766 47 RHP 1952 802 48 RHP 1952 802 48 RHP 1952 717 49 RHP 1952 803 1 WSM 1952 708 2 WSM 1952 708 2 WSM 1952 772 4 WSM 1952 772 4 WSM 1952 750 6 WSM 1952 750 12 WSM 1952 758	10 8 9 11 12 13 15 13 14 14 14 14 14 14 16 16 16
TT 48 DWP 1948  RESET 1953 794  TT 49 DWP 1948 771  TT 50 DWP 1948 705  TT 51 DWP 1948 750  TT 52 DWP 1948 721  TT 53 DWP 1948 702  TT 54 DWP 1948 666  TT 57 DWP 1948 482	6 6 7 7 8 8	NGS SIMPSONVILLE 1935 SIMPSONVILLE 1935 (Az. MI SIMPSONVILLE NO 1 1935 D 57 1935 G 57 1935 K 57 1935 V 122 1940	5,5,13 5,6,13 5,6,13 9 8,15 14

1006

1906	
ISOLATED BENCH MARKS (C. H. Semper, 1906; Book 7242; and E. C. Bibbee, 1910; Book A 8668)	<u>Feet</u>
Simpsonville, 3.8 mi E. of, along U. S. Highway 60-460, thence 1.2 mi N.; at Scotts; 27 ft W. of centerline of rd.; 6l ft NW. of centerline of Louisville and Nashville Railroad crossing; 14 ft NE. of telephone pole; 1 ft SE. of board fence; on iron post; standard cap stamped "750" (Tied by NGS, 1954)	749.844
Field, 0.2 mi W. of station; in W. abutment of RR. trestle; standard tablet stamped "725"	724.703
Conner, 50 ft S. of station; on E. side of rd. in angle with right-of-way; on iron post; standard cap stamped "701"	701.236
Long Run, 100 ft E. of station; 43 ft NE. of center- line of L. & N. RR. crossing Hobbs Road; 32 ft E. of centerline of rd.; 28 ft N. of N. rail; 20 ft S. of lone 30-in. maple tree; on iron post; standard cap stamped "629" (Tied by NGS, 1954)	629.188
Beckley, 0.3 mi SE. of station; in retaining wall of W. abutment of bridge S. of track; standard tablet stamped "595" (Reported not found, 1949)	594.974
Wilsonville, 2.7 mi NW. of, along State Highway 155; at SW. corner of crossroads; on iron post; standard cap stamped "600"	600.172
Waterford, 5.0 mi N. of; 375 ft S. of rd. forks; 15 ft W. of centerline of rd.; 1 ft W. of fence; on property of E. C. Rusk; on iron post; standard cap stamped "591"	591.326
Waterford, 1.7 mi N. of; at SW. corner of junction of T-rd. NW. near junction of Little Plum and Big Plum Creeks; on iron post; standard cap stamped "513" Reported Destroyed '78	513.351
Waterford, at NW. corner of residence of David Stump; under corner of porch; on iron post; standard cap stamped "468" (Enclosed porch has been built over BM - BM cannot be used unless portion of porch is torn down '78)	468.136

on SE. side of 40-in. oak tree; copper nail and

731.70

washer

TAYLORSVILLE Book AV 92

E. O. Miner

		1949	
	LINE 2.		Feet
E. O. Miner, 1949; Book AV	92		
Simpsonville; on lawn of of 91 ft N. of centerline of ft NE. of SE. corner of corner of lodge; 14 ft N concrete post; NGS standed disk stamped "SIMPSONVIL	f U.S. Highway 60-460 lodge; 24 ft SE. of NE W. of 6-in. ash tree; ard triangulation stat	; 35 • in ion	322.833
Reference mark NO. 1; 97 for of NW. corner of enclosed ft SE. of cistern pump; house; NGS standard reference; "SIMPSONVILLE NO 1 1935"	d porch of frame house l ft W. of small poult: rence mark disk stamped	; 54 ry i	322.902
Simpsonville, 38 ft SE. of Lodge building; 32 ft N. Highway 60-460; on iron stamped "PRIM TRAV STA N disturbed, 1952) (Tied	of centerline of U.S post; standard cap 0 1 1905 825" (Reporte	ed	B24.605
U.E., Simpsonville; at NW. concrete wingwall; chise		8	315.48
Simpsonville, 0.8 mi W. of 60-460; thence 0.9 mi N. of J. T. Wright; 8 ft SW ft S. and 16 ft E. of ce of drive N.; 1 ft W. of standard tablet stamped	; 600 ft S. of residend . of telephone pole; 6 nterline of rd. at jund fence; in concrete pos	ction t;	715.422
Reference mark; 460 ft S. abutment of bridge; chis			702.27
U.E., Simpsonville, 0.8 mi on SW. concrete retaining large creek; chiseled sq	g wall of bridge over		580.37
	LINE 3.		
E. O. Miner, 1949; Book AV	92		
"PRIM TRAV STA NO 1 1905 8	25" (Described in line	e 2)	324.605
"SIMPSONVILLE 1935" (NGS)	(Described in line 2	)	322.833

LINE 3 (Cont'd.)	Feet
"SIMPSONVILLE NO 1 1935" (NGS) (Described in line 2)	822.902
U.E., Simpsonville, l.l mi S. of; 35 ft SW. of cross-roads; in root on E. side of 12-in. locust tree; copper nail and washer	815.30
Simpsonville, 1.1 mi S. of, thence 0.5 mi W.; 0.2 mi W. of RR. crossing; 24 ft N. and 111 ft W. of centerline of rd. at junction of private drive S.; 245 ft N. of large brick farmhouse; 0.8 ft S. of hwy. right-of-way; in concrete post; standard tablet stamped "TT 48 DWP 1948 RESET 1953 794"	794.661
U.E., Simpsonville, l.l mi S. of, thence l.O mi W., thence 0.9 mi S.; at W. corner of two pipe culverts; on masonry wingwall; chiseled square	745.38
Simpsonville, 1.1 mi S. of, thence 1.0 mi W., thence 1.4 mi SW.; 2.5 mi E. of Clark; 13 ft S. and 490 ft W. of centerline of rd. at junction of Y-rd.; 500 ft E. of powerline crossing; 95 ft NW. of NW. corner of residence of E. Conn; 6 ft W. of fence corner; in concrete post; standard tablet stamped "TT 49 DWP 1948 771"	770.805
Reference mark; 530 ft E. of tablet; 190 ft E. of junction of Y-rd.; on W. end of N. concrete headwall of bridge; chiseled square	726.21
U.E., Clark, 0.9 mi SE. of, thence 0.6 mi E.; 40 ft NE. of centerline of rd. at junction of private T-rd. N.; in root on E. side of 36-in. oak tree; copper nail and washer	752.70
U.E., Clark, 0.9 mi SE. of, thence 0.2 mi E.; on E. end of N. concrete headwall of culvert; chiseled square	717.06
Clark, 0.9 mi SE. of, along State Highway 148; 30 ft W. of centerline of hwy. at junction of T-rd. E.; 25 ft N. of powerline pole; 2 ft N. of fenceline; in concrete post; standard tablet stamped	
"TT 50 DWP 1948 705"	704.385

## 171 KENTUCKY

TAYLORSVILLE

LINE 3 (Cont'd.)	Feet
U.E., Clark, O.3 mi E. of; between two halves of offset crossroad; on E. end of N. concrete headwall of bridge; chiseled square	665.47
Clark, 100 ft NW. of station; on N. side of RR. track at crossing; on iron post; standard cap stamped "685 KY"	684.602
U.E., Clark, 1.5 mi SE. of; 375 ft N.of intersection of offset crossroad; on N. end of W. concrete head-wall of culvert; chiseled square	722.82
U.E., Clark, 2.4 mi SE. of; 400 ft NW. of centerline of State Highway 148 at junction of Y-rd.; on NW. end of NE. concrete headwall of bridge; chiseled square	724.38
Clark, 3.0 mi SE. of, along State Highway 148; 4.5 mi W. of Finchville; 30 ft E. of centerline of hwy.; 150 ft SW. of white frame house; 6 ft W.of fenceline; 2 ft N. of power pole; in concrete post; standard tablet stamped "TT 51 DWP 1948 750"	749.810
Reference mark; 110 ft SW. of tablet; on N. end of W. concrete headwall of culvert; chiseled square	745.72
U.E., Finchville, 3.6 mi W. of, along State Highway 148; at SW. corner of concrete bridge over Plum Creek; on concrete abutment; chiseled square	667.46
Finchville, 2.5 mi W. of, along State Highway 148; 26 ft N. and 26 ft E. of centerline of hwy. at junction of T-rd. S.; 13 ft E. of junction of driveway N.; 5 ft E. of 12-in. locust tree; 2 ft S. of fence; in concrete post; standard tablet stamped "TT 52 DWP 1948 721"	720.352
Reference mark; 60 ft SW. of tablet; at NW. corner of bridge; on W. end of S. concrete headwall of culvert; chiseled square	719.31
U.E., Finchville, 2.5 mi W. of, thence 0.5 mi SE.; 30 ft NE. of centerline of crossroad; in root on S. side of 24-in. cedar tree; copper nail and washer	799•23

LINE 3 (Cont'd.)	Feet
U.E., Veech, 0.8 mi NW. of; 25 ft N. of centerline of State Highway 55 at intersection of crossroad; on concrete right-of-way post; chiseled square	711.84
Finchville, 2.3 mi S. of; at Veech; 48 ft W. of W. rail of main track; 38 ft S. of large oak tree; on iron post; standard cap stamped "3 D 1923 KY" (Tied by NGS, 1935)	673.322
"G 57 1935" (NGS)	679.703
Elk Creek, 1.0 mi N. of, along State Highway 55, thence 0.7 mi NE. along county rd. following creek; 27 ft N. of centerline of rd.; 300 ft NE. of farm house with red brick siding; 200 ft E. of creek; 54 ft E. of fence corner; in concrete post; standard tablet stamped "TT 53 DWP 1948 702"	701.916
Reference mark; 27 ft S. of tablet; on 2- by 4-ft exposure of ledge of rock; chiseled square	699.01
U.E., Elk Creek, 1.0 mi N. of; 35 ft NE. of centerline of State Highway 55 at junction of graveled rd. W.; on SW. end of NW. concrete headwall of culvert; chiseled square	684 <b>.</b> 94
U.E., Elk Creek; 200 ft NW. of centerline of State Highway 55 at junction of State Highway 155; on SE. concrete abutment of bridge over Elk Creek; chiseled square	666.01
Elk Creek, 200 ft NW. of church; 35 ft E. of center- line of State Highway 55; 28 ft W. of tombstone of Dr. F. B. Collins; 3 ft S. of telephone pole; in concrete post; standard tablet stamped "TT 54 DWP 1948 666"	666,295
U.E., Elk Creek, 0.6 mi S. of; at NW. corner of concrete bridge over Elk Creek; on abutment; chiseled square	644.30
Elk Creek, 0.8 mi S. of, along State Highway 55, thence 1.2 mi SW. along Elk Creek Road; 15 ft W. of centerline of rd.; 110 ft S. of bridge over small stream; in concrete post; standard tablet stamped "54 EOM 1949 612"	612.197

487.95

-1- 11-11-00111	
LINE 4 (Cont'd.)	Feet
Taylorsville, 0.3 mi S. of, along State Highway 55, thence 1.5 mi SW. along river rd.; on S. bank of Salt River; 0.5 mi SW. of Darling Company office; 900 ft S. of house; 21 ft S. and 14 ft E. of centerline of rd. at junction of drive E.; 24 ft E. of 36-in. sycamore tree; 7 ft S. of telephone pole; in concrete post; standard tablet stamped "TT 57 DWP 1948 482"	481.469
Reference mark; 55 ft NW. of tablet; in S. base on S. side of 24-in. elm tree; spike nail	478.45
U.E., Taylorsville, 0.3 mi S. of, thence 3.1 mi SW.; 30 ft S. of centerline of rd. at junction of private rd.; 15 ft E. of center of small bridge; in base on W. side of 24-in. elm tree; spike	503.82
Taylorsville, 0.3 mi S. of, along State Highway 55, thence 3.5 mi SW.; 15 ft E. of centerline of rd.; 250 ft N. of residence of John W. Harrison; 6 ft NW. of 18-in. elm tree; in concrete post; standard tablet stamped "TT 58 DWP 1948 619"	619.370
Reference mark; 64 ft NE. of tablet; 15 ft SE. of centerline of rd.; on rock ledge; chiseled square	614.89
$\sqrt{J}$ ogs into Bardstown quadrangl $\underline{e}$ 7	
U.E., Highgrove, 4.2 mi E. of, thence 1.2 mi N.; 25 ft W. of ford; in root on NE. side of 36-in. sycamore tree; copper nail and washer	479.03
LINE 5.	
E. O. Miner, 1949; Book AV 92	
U.E., Elk Creek; chiseled square (Described in line 3)	666.01
U.E., Elk Creek, 0.5 mi NW. of; on NW. end of NE. concrete headwall of culvert under State Highway 155; chiseled square	693.07

### LINE 5 (Cont'd.) Feet Elk Creek, 1.8 mi NW. of, along State Highway 155; 0.9 mi SE. of Wilsonville; 45 ft S. of, and 9 ft lower than centerline of hwy. at junction of T-rd. S.; in triangle; in concrete post; standard tablet stamped "56 EOM 1949 687"Reported Destroyed 178 686.735 Reference mark; 0.3 mi E. of tablet; on E. end of S. concrete headwall of culvert; chiseled square 711.01 U.E., Wilsonville; at E. edge of; on SE. end of NE. concrete headwall of culvert; chiseled square 671.96 Wilsonville; at intersection of State Highway 155 and Waterford Pike; at SW. corner of yard of E. Alcorn; on iron post; standard cap stamped "642 KÝ" 642.261 U.E., Wilsonville, 0.5 mi SW. of, thence 0.9 mi NW.; at Jefferson-Spencer County line; on SW. concrete headwall of bridge over Drakes Branch; chiseled square 653.78 Wilsonville, 0.5 mi SW. of, thence 1.5 mi NW.; 30 ft SW. of centerline of rd. at junction of drive S.; 1 ft N. of fence; in concrete post; standard tablet stamped "57 EOM 1949 756" 755.435 Reference mark; 115 ft E. of tablet; 15 ft N. of centerline of rd.; in root on SW. side of 24-in. coffee tree; copper nail and washer 755.56 U.E., Wilsonville, O.5 mi SW. of, thence 3.2 mi W.; at Routt; 15 ft S. and 80 ft E. of centerline of rd. at junction of T-rd. E.; in root on S. side of 24-in. cedar tree; spike 673.15 Wilsonville, 0.5 mi SW. of, thence 3.2 mi W., thence 0.5 mi S.; 0.5 mi S. of Routt; 46 ft N. and 40 ft W. of centerline of rd. at junction of T-rd. W.; in concrete post; standard tablet stamped "58 EOM 1949 RESET 1954 729" 729.153 Reference mark; 5 ft S. of tablet; in root on S. side of 12-in. locust tree which serves as corner fencepost; spike 727.43

# 171 KENTUCKY

TAYLORSVILLE

TAT KENTOCKI	
LINE 5 (Cont'd.)	Feet
U.E., Routt, 0.5 mi S. of, thence 0.5 mi W.; on W. corner of concrete wingwall of bridge over Brush Run; chiseled square	660.42
U.E., Routt, 0.5 mi S. of, thence 0.5 mi W.; thence 1.0 mi SW.; 35 ft NW. of centerline of rd. at junction of drive S.; on SW. concrete headwall of bridge; chiseled square	589 <b>.</b> 21
LINE 6.	
E. O. Miner, 1949; Book AV 92	
"685 KY" (Described in line 3)	684.602
U.E., Clark, 1.0 mi SW. of; 170 ft W. of crossroads; on E. end of N. concrete headwall of culvert; chiseled square	618.34
Clark, 1.6 mi W. of, along State Highway 148, thence 0.5 mi NW. along State Highway 155; 0.4 mi E. of Fisherville; 135 ft SE. of centerline of Highway 155 at junction of Eastwood Road; 24 ft NE. of centerline of hwy.; in concrete post; standard tablet stamped "59 EOM 1949 564" (Reported not found, 1960)	563.510
U.E., Fisherville; at N. corner of steel hwy. bridge over Floyds Fork; on concrete bridge seat; chiseled square	559•39
U.E., Fisherville, 0.5 mi W. of; 120 ft NW. of center- line of State Highway 155 at junction of English Station Road; on E. end of N. concrete headwall of culvert; chiseled square	556.01
Fisherville, 1.5 mi W. of, along State Highway 155; 4.7 mi E. of Jeffersontown; 20 ftS. and 55 ft E. of centerline of hwy. at junction of T-rd. S.; 2 ft E. of telephone line brace pole; in concrete post; standard tablet stamped "60 EOM 1949 546"	545.485
Reference mark; 430 ft W. of tablet; on NE. concrete wingwall of bridge over Poke Lick Creek; chiseled square	548.00

/Jogs into La Grange quadrangle/

LINE 8 (Cont'd.)	Feet
Simpsonville, 2.2 mi NE. of, thence 1.1 mi E.; 21 ft SW. of centerline of graveled rd. at junction of drive S., 30 ft NW. of center of cattle guard in line with rd. E.; 5 ft SE. of corner fencepost; 1 ft NE. of fence; in concrete post; standard tablet stamped "47 RHP 1952 802"	801.224
U.E., Simpsonville, 3.8 mi E. of, along U. S. Highway 60-460, thence 1.7 mi N., thence 0.4 mi W.; in center of wooden floor of bridge over Bullskin Creek; copper nail and washer	704.16
Simpsonville, 3.8 mi E. of, along U. S. Highway 60-460, thence 1.7 mi N.; at Shiloh Church; 240 ft N. of, and 5 ft lower than centerline of rd. at junction of Y-rd.; 120 ft W. of junction of graveled rd. NE.; 107 ft NE. of graveled rd. NW.; 2 ft NW. of NW. corner of church; in concrete post; standard tablet stamped "48 RHP 1952 717"	716.242
Reference mark; on NE. corner of top concrete step of Shiloh Church; chiseled square	716.93
Shelbyville, 2.8 mi NW. of, along State Highway 53, thence 1.0 mi W.; 12 ft S. and 20 ft E. of centerline of rd. at junction of farm rd. S.; 3 ft SW. of corner fencepost; in concrete post; standard tablet stamped "49 RHP 1952 803"	802.207
LINE 9.	
W. S. Monk, 1952; Book AV 334	
"K 57 1935" (NGS)	705.894
Simpsonville, 2.4 mi S. of, thence 2.4 mi E.; 0.2 mi E. of Bullskin Creek; 15 ft S. and 31 ft W. of centerline of Brunerstown Road at junction of drive S.; in concrete post; standard tablet stamped "1 WSM 1952 708"	708.025
Simpsonville, 2.4 mi S. of, thence 0.3 mi E.; 20 ft N. and 30 ft E. of centerline of Brumerstown Road at junction of T-rd. E.; in concrete post; standard tablet stamped "2 WSM 1952 749"	748.928

566.834

501.598

"4 WSM 1952 502" (Described in line 10)

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

38-085-23
TAYLORSVILLE QUADRANGLE
171 KENTUCKY
N3800-W8515/15
DIAGRAM NJ 16-6
LOUISVILLE

Bullitt, Jefferson, Shelby, and Spencer Counties

Edition of 3/15/77

PR: CRV/rmm

Plane coordinates are based on Lambert projection, Kentucky, North Zone

Only the permanent marks are listed for control classified obsolete and are not shown on sketch

LA GRANGE (188)

LOUISVILLE (172) ■ Taylorsville

MOUNT EDEN (170)

389001

BARDSTOWN (148)

# INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
750 PTS NO 1 1905 825 PTS NO 4 1905 489 1 D 1923 KY 490 IT 40 DWP 1948 716 IT 48 DWP 1948 RESET 1953 794 IT 49 DWP 1948 771 IT 50 DWP 1948 705 IT 51 DWP 1948 750 IT 52 DWP 1948 721 IT 53 DWP 1948 702 IT 54 DWP 1948 666 IT 55 DWP 1948 IT 56 DWP 1948 IT 56 DWP 1948 IT 57 DWP 1948 619 IT 34 AS 1950 IT 35 AS 1950 IT 36 AS 1950 728 3 WSM 1952 772 IT 4 WSM 1952 750 IT 12 WSM 1952 758 IT	3634333344444455555566

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11

LONGITUDE 0 1 11

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By C. B. Kendall, 1905; Books A 27, 28, 29, 30

Laylorsville; in SW. corner of yard of Spencer County Court House; on iron pipe; standard cap stamped "PRIM TRAV STA NO 4 1905 489"

X = 1,684,627 Y = 195,336

38 01 52.55

85 20 41.63

Simpsonville, 3.8 mi E. of, along U. S. Highway 60-460, thence 1.2 mi N.; at Scotts; 27 ft W. of centerline of rd.; 61 ft NW. of centerline of Louisville and Mashville Railroad crossing; 14 ft NE. of telephone pole; 1 ft SE. of board fence; on iron post; standard tablet stamped "750"

X = 1.702.442

Y = 268.970

38 14 02.48

85 17 09.34

By D. W. Pinkston, 1948; Book AH 122

Simpsonville, 1.1 mi S. of, thence 0.5 mi W.; 0.2 mi W. of RR. crossing; 24 ft N. and 111 ft W. of centerline of rd. at junction of private drive S.; 245 ft N. of large brick farmhouse; 0.8 ft S. of hwy. right-of-way; in concrete post; standard tablet stamped "TT 48 DWP 1948 RESET 1953 794"

X = 1.681.201

Y = 259.128

38 12 22,75

85 21 34.04

Simpsonville, 0.8 mi W. of, along U. S. Highway 60-460, thence 0.9 mi N. along graveled rd.; 6 ft S. and 16 ft £. of centerline of rd. at junction of drive N.; 600 ft S. of residence of J. T. Wright; 8 ft SW. of telephone pole: 1 ft W. of fence; in concrete post; standard tablet stamped "TT 40 DWP 1948 716"

X = 1,678,218

Y = 270.290

38 14 12.73

85 22 13,12

Simpsonville, 1.1 mi S. of, thence 1.0 mi W., thence 1.4 mi SW.; 2.5 mi E. of Clark; 500 ft E. of powerline crossing: 13 ft S. and 490 ft W. of centerline of rd. at junction of Y-rd.; 95 ft NW. of NW. corner of residence of Ed Coon; 6 ft W. of fence corner; 1 ft N. of fence; in concrete post; standard tablet stamped "TT 49 DWP 1948 771"

X = 1.676.414 Y = 252.176

38 11 13.45

85 22 32.94

Clark. 0.9 mi SE. of, along State Highway 148; 30 ft W. of centerline of hwy. at junction of I-rd. E.; 25 ft N. of power pole; 2 ft N. of fenceline; in concrete post; standard tablet stamped "TT 50 DWP 1948 705"

X = 1.667.907 Y = 250.788

38 10 58.69

85 24 19.28

Clark, 3.0 mi SE. of, along State Highway 148; 4.5 mi W. of Finchville; 30 ft E. of centerline of hwy.; 150 ft SW. of white frame house; 6 ft W. of fenceline; 2 ft N. of power pole; in concrete post; standard tablet stamped "TT 51 DWP 1948 750"

X = 1.673.922

Y = 242.061

38 09 33.16

85 23 02.60

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE 0 1 17

#### OBSOLETE MARKS (Cont'd.)

Finchville, 2.5 mi W. of, along State Highway 148; 26 ft N. and 26 ft E. of centerline of hwy. at junction of I-rd. S.; 13 ft E. of junction of drive N.; 5 ft E. of 12-in. locust tree; 2 ft S. of fence; in concrete post; standard tablet stamped "TT 52 DWP 1948 721"

X = 1.680.966

Y = 236.513

38 08 39.16

85 21 33,58

Elk Creek, 1.0 mi N. of, along State Highway 55, thence 0.7 mi NE. along county rd. following creek; 27 ft N. of centerline of rd.; 300 ft NE. of farm residence with red brick siding; 200 ft E. of creek; 54 ft E. of fence corner; in concrete post; standard tablet stamped "TT 53 DWP 1948 702"

X = 1.681.480

Y = 227.862

38 07 13,71

85 21 25.83

Elk Creek; 200 ft NW. of church; 35 ft E. of centerline of State Highway 55; 28 ft W. of tombstone of Dr. F. B. Collins; 3 ft S. of telephone pole; in concrete post; standard tablet stamped "TT 54 DWP 1948 666"

X = 1.677.658 Y = 219.004

38 05 45-69

85 22 12.32

Taylorsville, 4.0 mi N. of, along State Highway 55; 2.0 mi S. of Elk Creek; 225 ft SE. of large farmhouse on hill; 28 ft E. of centerline of hwy.; 43 ft S. of SW. corner of barn; in concrete post; standard tablet stamped "TT 55 DWP 1948"

X = 1.681.105

Y = 211.013

38 04 27.11

85 21 27.99

Taylorsville, 2.0 mi N. of, along State Highway 55; 4.0 mi S. of Elk Creek; 29 ft E. of centerline of hwy.; 120 ft SW. of residence of H. C. Spencer; 38 ft S. of yard fence; in concrete post; standard tablet stamped "TT 56 DWP 1948"

X = 1.679.967 Y = 199.806

38 02 36.19

85 21 40.53

Taylorsville; at S. entrance to Spencer County Court House; in SE. corner of bottom step; standard tablet stamped "1 D 1923 KY 490"

X = 1,684,609 Y = 195,319

38 01 52.38

85 20 41.85

Taylorsville, 0.3 mi S. of, along State Highway 55, thence 1.5 mi SW. along River Road; on S. bank of Salt River; 0.5 mi SW. of Darling Company Office; 900 ft S. of house; 21 ft S. and 14 ft E. of centerline of rd. at junction of drive E.; 24 ft E. of 36-in. sycamore tree; 7 ft S. of telephone pole; in concrete post; standard tablet stamped "TT 57 DWP 1948 482"

X = 1.681.683

Y = 188.357

38 00 43.21

85 21 17.36

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 9 11

LONGITUDE 0 1 17

## OBSOLETE MARKS (Cont'da)

Taylorsville, 0.3 mi S. of, along State Highway 55, thence 3.5 mi SW.; 15 ft E. of centerline of rd.; on S. side of Salt River; 250 ft N. of residence of John W. Marrison; 6 ft NW. of 18-in. elm tree; in concrete post; standard tablet stamped "TT 58 DWP 1948 619"

X = 1.674.951

Y = 185.311

38 00 12.30

85 22 41.01

By A. Salloom, 1950; Book AH 194

Taylorsville, 2.6 mi E. of, along State Highway 44; 33 ft S. and 38 ft E. of intersection of State Highways 44 and 248; 28 ft S. of centerline of Highway 248; 37 ft S. of centerline of Highway 44; 17 ft SW. of hwy. marker; 2 ft N. of fenceline; in concrete post; standard tablet stamped "TT 34 AS 1950" (Reported destroyed, 1953)

X = 1,696,894 Y = 195,629

38 01 56.86

85 18 08.36

Taylorsville, 2.6 mi E. of, along State Highway 44, thence 2.4 mi SE. along State Highway 248; 19 ft N. and 27 ft W. of traingle formed by junction of I-rd. N.; 39 ft N. of centerline of hwy.; 46 ft NW. of mailbox of Willie Bently; in concrete post; standard tablet stamped "TT 35 AS 1950" (Reported destroyed, 1953)

X = 1.706.400

Y = 189.988

38 01 02.16

85 16 08.80

Taylorsville, 2.6 mi E. of, along State Highway 44, thence 2.3 mi SE. along State Highway 248, thence 1.6 mi SW.; 0.8 mi N. of Ash Creek; 15 ft N. and 11 ft E. of center of grassy triangle formed by junction of I-rd. SE.; 19 ft SE, of NE, corner fencepost in E, corner of land owned by Mr. Nannie Donovan; 10 ft S. of 24-in. locust tree; in concrete post; standard tablet stamped "TT 36 AS 1950 728"

X = 1.704.401

Y = 184,841

38 00 11.06

85 16 33.05

By J. R. Harris, 1953; Book AH 300

Taylorsville, 2.6 mi E. of, along State Highway 44; 30 ft N. and 90 ft W. of centerline of Highway 44 at junction of State Highway 248; 120 ft N. of NE. corner of residence on S. side of hwy.; in concrete post; standard tablet stamped "3 WSM 1952 772 II"

X = 1,696,906 Y = 195,694

38 01 57.51

85 18 08.22

Taylorsville, 2.6 mi E. of, along State Highway 44, thence 2.3 mi SE. along State Highway 248; 50 ft N. and 110 ft W. of centerline of hwy. at junction of rd. N.; 55 ft W. of drain crossing; in concrete post; standard tablet stamped "4 WSM 1952 502 II"

X = 1.706.283

Y = 190.027

38 01 02.53

85 16 10.25

STATION

ON DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE

#### OBSOLETE MARKS (Cont'd.)

By T. W. Cayce, 1953; Book AH 302

Olive Branch Church, 0.7 mi NE. of; 6.7 mi SW. of Shelbyville; 20 ft S. and 45 ft E. of centerline of rd. at junction of rd. SE.; in concrete post; standard tablet stamped "7 WSM 1952 750 II"

X = 1,711,748

V = 231,472

38 07 52.82

85 15 07.60

Little Mount; 30 ft S. and 25 ft W. of crossroads; 80 ft N. of NE. corner of stone house; in concrete headwall of culvert; standard tablet stamped "12 WSM 1952 758 IT"

X = 1,711,695

Y = 206.033

38 03 41.34

85 15 04.81

#### MARK TIED BY NGS

By C. B. Kendall, 1905; Books A 27, 28, 29,,30

Simpsonville; 38 ft SE. of SE. corner of Masonic Lodge building; 32 ft N. of centerline of U. S. Highway 60-460; on iron pipe; standard cap stamped "PRIM TRAV STA NO 1 1905 825" (Reported disturbed, 1952)

X = 1,681,317.00 Y

Y = 265,086.77

38 13 21.662

85 21 33.492

#### DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered <u>OBSOLETE</u> and is included in this list for the purpose of identification only.